

Amendments to the Claims

1. (currently amended) A coordinated push synchronization method, comprising the acts of:

detecting changes to a local application data store;
identifying a record affected by a detected change;
pushing the identified record to a remote application data store;
ascertaining whether the identified pushed record, in its current form as affected by the detected change, has been replicated or deleted in a the remote application data store through user-initiated synchronization; and
if not, updating the remote application data store with the pushed record;
after updating, identifying the pushed record in the remote application data store as a pushed record.

2. (currently amended) The method of Claim 1, wherein the act of ascertaining includes comparing a local change counter associated with the pushed record in the local application data store with a remote change counter associated with a corresponding record in the remote application data store, ~~where values for the local and remote change counters are equal the identified record, in its current form, has been replicated or deleted through user-initiated synchronization.~~

3. (original) The method of Claim 1, wherein the act of pushing the identified record comprises:

if the identified record has been detected as being new, pushing a replica of the identified record with instructions to save the replica in the remote application data store;

if the identified record has been detected as being modified, pushing a replica of the identified record with instructions to save the replica in the remote application data store replacing a prior version of the record; and

if the identified record has been detected as being deleted, pushing instructions to delete a prior version of the identified contained in the remote application data store.

4. (currently amended) The method of Claim 1, ~~further comprising, after updating the remote application data store, setting a coordination flag for the pushed record wherein the act of identifying comprises associating an indicator with the pushed record identifying the pushed record in the remote application data store as a pushed record.~~

5. (currently amended) A coordinated user-initiated synchronization method, comprising the acts of:

detecting changes to a local application data store;
identifying a record affected by a detected change;
ascertaining whether the identified record, in its current form as affected by the detected change, ~~has been pushed into the local application data store replicated in-or-deleted from a remote application data store through push synchronization;~~ and
if not, synchronizing the remote application data store with the local application data store.

6. (currently amended) The method of Claim 5, wherein the act of ascertaining includes examining ~~an indicator associated with a pushed record identifying the pushed record in the remote application data store as a pushed record-a coordination flag associated with the identified record, a set coordination flag indicating that the identified record, in its current form, has been replicated in-or-deleted from the remote application data store through push synchronization and a reset coordination flag indicating that the identified record, in its current form, has not.~~

7. (original) The method of Claim 5, wherein the act of synchronizing comprises:

if the identified record has been detected as being new, replicating the identified record in the remote application data store;
if the identified record has been detected as being modified, replicating the identified record in the remote application data store replacing a prior version of the

record; and

If the identified record has been detected as being deleted, deleting the version of the identified record from the remote application data store.

8. (cancelled)

9. (cancelled)

10. (currently amended) A coordinated push and user-initiated synchronization method, comprising:

detecting changes to a local application data store;

identifying a first record in the local application data store affected by a detected change;

pushing the first record to a remote application data store;

~~if the identified record is pushed, ascertaining whether the identified pushed record, in its current form as affected by the detected change, has been replicated in or deleted from a the remote application data store through user-initiated synchronization and, if not, updating the remote application data store with the pushed record;~~

detecting changes to the remote application data store;

identifying a second record in the remote application data store affected by a detected change;

~~if a user initiates synchronization, ascertaining whether the identified second record, in its current form as affected by the detected change, has been pushed into the replicated in or deleted from a remote application data store through push synchronization and, if not, synchronizing the remote application data store with the local application data store.~~

11. (currently amended) The method of Claim 10, wherein the act of ascertaining whether the identified pushed record has been replicated in or deleted from a the remote application data store through user-initiated synchronization

includes comparing a local change counter associated with the identified pushed record in the local application data store with a remote change counter associated with a corresponding record in the remote application data store, the identified record, in its current form, has been replicated or deleted through user-initiated synchronization where values for the local and remote change counters are equal.

12. (currently amended) The method of Claim 10, wherein the act of ascertaining whether the identified pushed record has been replicated in or deleted from the remote application data store ~~through push synchronization~~ includes examining an indicator associated with the pushed record identifying the pushed record in the remote application data store as a pushed record a coordination flag associated with the identified record, a set coordination flag indicating that the identified record, in its current form, has been replicated in or deleted from the remote application data store ~~through push synchronization~~ and a reset coordination flag indicating that the identified record, in its current form, has not.

13. (cancelled)

14. (cancelled)

15. (currently amended) The method of Claim 10, further comprising, after updating the remote application data store with the pushed record, identifying the pushed record in the remote application data store as a pushed record setting a coordination flag associated with the pushed record.

16. (cancelled)

17. (currently amended) A coordinated push synchronization computer program product comprising a computer useable medium having computer readable instructions thereon for:

detecting changes to a local application data store;
identifying a record affected by a detected change;

pushing the identified record to a remote application data store;

ascertaining whether the identified pushed record, in its current form as affected by the detected change, has been replicated or deleted in a the remote application data store ~~through user-initiated-synchronization~~; and

if not, updating the remote application data store with the pushed record;
after updating, identifying the pushed record in the remote application data store as a pushed record.

18. (currently amended) The product of Claim 17, wherein the instructions for ascertaining include instructions for comparing a local change counter associated with the pushed record in the local application data store with a remote change counter associated with a corresponding record in the remote application data store, where values for the local and remote change counters are equal the identified record, ~~in its current form, has been replicated or deleted through user-initiated synchronization.~~

19. (original) The product of Claim 17, wherein the instructions for pushing the identified record comprise instructions for:

if the identified record has been detected as being new, pushing a replica of the identified record with instructions to save the replica in the remote application data store;

if the identified record has been detected as being modified, pushing a replica of the identified record with instructions to save the replica in the remote application data store replacing a prior version of the record; and

if the identified record has been detected as being deleted, pushing instructions to delete a prior version of the identified contained in the remote application data store.

20. (currently amended) The product of Claim 17, further comprising instructions for, after updating the remote application data store with the pushed record, setting a coordination flag for the pushed record wherein the instructions for identifying comprises instructions for associating an indicator with the pushed record

identifying the pushed record in the remote application data store as a pushed record.

21. (currently amended) A coordinated user-initiated synchronization computer program product comprising a computer useable medium having computer readable instructions thereon for:

detecting changes to a local application data store;

Identifying a record affected by a detected change;

ascertaining whether the identified record, in its current form as affected by the detected change, has been pushed into the local application data store replicated in or deleted from a remote application data store through push synchronization; and

if not, synchronizing the remote application data store with the local application data store.

22. (currently amended) The product of Claim 21, wherein the instructions for ascertaining include instructions for examining an indicator associated with a pushed record identifying the pushed record in the remote application data store as a pushed record-a coordination flag associated with the identified record, a set-coordination flag indicating that the identified record, in its current form, has been replicated in or deleted from the remote application data store through push synchronization and a reset-coordination flag indicating that the identified record, in its current form, has not.

23. (original) The product of Claim 21, wherein the instructions for synchronizing comprise instructions for:

if the identified record has been detected as being new, replicating the identified record in the remote application data store;

if the identified record has been detected as being modified, replicating the identified record in the remote application data store replacing a prior version of the record; and

If the identified record has been detected as being deleted, deleting the

version of the identified record from the remote application data store.

24. (cancelled)

25. (cancelled).

26. (currently amended) A coordinated push and user-initiated synchronization computer program product comprising a computer useable medium having computer readable instructions thereon for:

detecting changes to a local application data store;

identifying a first record in the local application data store affected by a detected change;

pushing the first record to a remote application data store;

if the identified record is pushed, ascertaining whether the identified pushed record, in its current form as affected by the detected change, has been replicated in or deleted from a the remote application data store through user-initiated synchronization and, if not, updating the remote application data store with the pushed record;

detecting changes to the remote application data store;

identifying a second record in the remote application data store affected by a detected change;

if a user-initiates synchronization, ascertaining whether the identified second record, in its current form as affected by the detected change, has been pushed into the replicated in or deleted from a remote application data store through push synchronization and, if not, synchronizing the remote application data store with the local application data store.

27. (currently amended) The product of Claim 26, wherein the instructions for ascertaining whether the identified pushed record has been replicated in or deleted from a the remote application data store through user-initiated synchronization include instructions for comparing a local change counter associated with the identified pushed record in the local application data store with a remote change

counter associated with a corresponding record in the remote application data store, the identified record, in its current form, has been replicated or deleted through user-initiated synchronization where values for the local and remote change counters are equal.

28. (currently amended) The product of Claim 26, wherein the instructions for ascertaining whether the identified pushed record has been been replicated in or deleted from the remote application data store through push synchronization include instructions for examining an indicator associated with the pushed record identifying the pushed record in the remote application data store as a pushed record-a coordination flag associated with the identified record, a set coordination flag indicating that the identified record, in its current form, has been replicated in or deleted from the remote application data store through push synchronization and a reset coordination flag indicating that the identified record, in its current form, has not.

29. (cancelled)

30. (cancelled)

31. (original) The product of Claim 26, further comprising instructions for, after updating the remote application data store with the pushed record, identifying the pushed record in the remote application data store as a pushed record setting a coordination flag associated with the pushed record.

32. (cancelled)

33. (cancelled)

34. (cancelled)

35. (cancelled)

36. (cancelled)

37. (cancelled)

38. (cancelled)

39. (cancelled)

40. (cancelled)

41. (cancelled)

42. (cancelled)

43. (cancelled)

44. (cancelled)

45. (cancelled)

46. (cancelled)

47.(new) The method of Claim 4, wherein the act of associating comprises setting a coordination flag for the pushed record.

48.(new) The method of Claim 6, wherein the indicator comprises a coordination flag, a set coordination flag indicating that a record is a pushed record and a reset coordination flag indicating that the record is not a pushed record.